

FTTH OTO with Translucent cover

DESCRIPTION

Made from high impact ABS plastics, these customer outlets are widely used in access networks and FTTH applications. The outlets can be used for both surface-mount and concealed panel installations.

FEATURES

- Wall-mounted
- Clip on – clip off lid
- Easy protection from the dust
- Multiple cable entries
- Existed in 1 or 2 LC/SC Adapters

APPLICATIONS

- FTTH → FTTO
→ Connecting point → Industrial



SPECIFICATIONS

Parameter	Value
Size (H*W*D) mm	86*115*23
Color	White
Material	ABS+PC
Capacity (Fibres)	1,2,4
Connect Models	Splicing, Mechanical Connector, FMC
Installation Models	Wall Mounted
Pigtail	G.657 Φ 0.9mm, 0.5m Or customer request
Drop cable(Flat)	Indoor Flat Drop cable 2mm*3mm
Drop cable (Round)	Φ 5mm~ Φ 7mm
Curvature Radius(mm)	\geq 15
Working Temp.	-25°C~+60°C
Storage Temp.	-40°C~+70°C
Air pressure	70Kpa-105Kpa

ORDERING INFORMATION

Description	Reference
OTO with translucent cover,1F, SC adapters with shutter	510221000000