

Indoor OTO Unwinding Kits Pushable Cable

DESCRIPTION

The unwinding OTO Kit is made up of a box with socket and optical fiber(from 1 to 4 fibers) with different length. Easy to operate, it is an economic choice to build the fiber home network.

FEATURES

- Material: Corrugated cardboard
- Color: Yellow
- Fast unwinding of the OTO and it's preconnectorized cable
- Suitable for E2000, SC, SC Apc, LC and LC Apc
- Simple structure and easy operation

APPLICATIONS

- FTTH, subscriber access
- FTTO/POL
- Industrial



SPECIFICATIONS

Parameter	value
Number of cable entries	5 entries (cable incoming from PBO) : 1 rear, 2 top, 1 left, 1 right
Applicable mode	G657A2
Number of cores	1F, 2F, 4F
LSZH outer sheath	4.7 mm
Color	White
Loose buffer diameter	0.9±0.05mm
Max. Tension (N)	40N (long term), 80N (short term)
Max. Crushing Resistance(N/100mm)	500N (long term), 1000N (short term)
Length	20/30/50/100/150M
Dimensions	220 x 200 x 64 mm
Euroclass	Dca-s2, d2, a2 or better
Adapter type	SC/APC
Box Max. dimension	80(L)x80(l)x40(H)mm
Optical performance	IL < 0,3 dB, RL ≥ 60 dB (APC)
IP performance	IP40
Impact resistance	IK07
Fire resistance	UL94 V0
DIN Box Material	ABS-PC
Operating temperature	-10°C-+60°C

ORDERING INFORMATION

Description	Reference