

12F MPO/ MTP® to 6x Duplex LC Fanout Cable 2.0mm

DESCRIPTION

MTP/MPO both side or with fan out to offer an easy connection with the patch panel or the network deviser in a data center or any place with concentrate quantity of fiber optic connection. Termination can be adapted as your requirement, 900um, 2mm or 3mm.

FEATURES

- Compact design
- Up to 24 fibers
- MTP/MPO per connector
- Easy to install, high fiber density cabling solution
- Male or female MTP/MPO connectors available
- Can be used with ribbon cable or micro cable
- Cable from 4F to 144F
- CPR upon request



APPLICATIONS

- Data center
- Lan/Wan networks
- POL
- Broadband

SPECIFICATIONS

| General | Values | | | | | |
|-------------------------------|----------------------|--------|------------|------------|---------|------------|
| Model | Standard | | | Premium | | |
| Connector Type | Singlemode | | Multi-mode | Singlemode | | Multi-mode |
| | UPC | APC | | UPC | APC | |
| Insertion Loss (each channel) | ≤0.5dB | ≤0.5dB | ≤0.5dB | ≤0.35dB | ≤0.35dB | ≤0.35dB |
| Return Loss (each channel) | ≤40dB | ≤55dB | / | ≤40dB | ≤55dB | / |
| Test Wavelength | 1310nm | | | 850nm | | |
| Durability | ≤0.2dB at 200 cycles | | | | | |
| Operating Temperature | -20° C~+70° C | | | | | |

ORDERING INFORMATION

| Description | Reference |
|-------------|-----------|
| | |