

Dual Door Wall Mounted Distribution Box 12-48 Fiber

DESCRIPTION

With double doors (key on option) will you easily manage the access of the installation part and user part. Many organizations can be imagined as managing PLC splitter or just terminate cable.

These wall mount enclosures for fiber optic patching are a great economic solution for a quick budget minded network. Easy to install and maintain, these patch panel wall mounts are a no brainer when it comes to making a decision about patch panels.

FEATURES

- Ability to independently lock either side of demarcation for security
- 8 LGX panel spaces and 5-tray capacity
- Pre-installed splice-tray mount, riser, & cable management rings
- Compatible tandem door & tube-distribution unit
- Raised splice tray mounting allows clearance for fiber routing
- Removal tray mount and management rings allow for cassettes to be used
- Knock-out access point available for back entry



APPLICATIONS

→ FTTX → FTTO & POL → LAN/WAN → CATV & Security

SPECIFICATIONS

Item	Characteristics
Operation Temperature	-25° C~+40° C
Storage Temperature	-25° C~+40° C
Relative Humidity	≤85%(+30° C)
Air Pressure	70kPa~106kPa
GPX10W1-12 Dimensions (WxDxH)	400mmx380mmx80mm
GPX10W1-24 Dimensions (WxDxH)	400mmx380mmx80mm
GPX10W1-48 Dimensions (WxDxH)	400mmx380mmx120mm

ORDERING INFORMATION

Description	Reference