

12F Distribution Box IP66

DESCRIPTION

Access termination box is able to hold up to 12 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

FEATURES

- Water-proof design with IP-66 Protection level.
- Integrated with splice cassette and cable management rods.
- Manage fibers in a reasonable fiber radius condition.
- Easy to maintain and extend the capacity.
- Fiber bend radius control more than 40mm.
- Suitable for the fusion splice or mechanical splice.
- 1*8 Splitter can be installed as an option.
- Efficient cable management.
- 12 ports cable entrance for drop cable.

APPLICATIONS

- Telecom
- FTTH
- LAN/WAN



SPECIFICATIONS

| Parameter | Value |
|----------------|-----------------------|
| Max. Capacity | 12SC/24LC/1x8 SC PLC |
| Size(LxWxH mm) | 250x200x72 |
| Max. Ratio | 1:8 |
| Mount Type | Wall or Pole Mounting |
| Connector Loss | ≤0.5dB |

ORDERING INFORMATION

| Description | Reference |
|--|-------------|
| Splitter Distribution Box with 1x8 Splitter 8 SC adapter IP66 IK10 | K3111000001 |