

Fiber optic waterproof box

DESCRIPTION

FTTX Enclosure is a new economic fiber distributed solution for outdoor use. Compare traditional products, FTTX Enclosure is easy to operate and has high compatibility. It can be used for wall-mounting, aerial installation or holding pole installation, based on different situation. FTTX Enclosure not only used in FTTH field, but also used in FTTA or other harsh environment.

FEATURES

- Plug and play, FastConnect drop cable instead of splicing, be installed without opening the closure.
- FastPlug realizes cable fastening and sealing outside the closure, leads to fast installation.
- Support pole/wall mounting, aerial cable mounting.
- Small size and elegant appearance.
- IP68 protection.
- High compatibility: can be assembled ODVA, SuperTap (OptiTap compatible), Mini SC or power adapter.
- Available with PLC or splice sleeve for fiber divide.



APPLICATIONS

→ FTTH → FTTA → Distribution network

SPECIFICATIONS

Item	Parameters
Dimension L×W×H	365*137*90mm(Without cover) 375×142×120mm(With cover)
Cable type	Hybrid or non-hybrid
Round cable OD	5.0mm to 14mm
Flat cable dimension	4.6×8.9mm
Cable jacket material	LSZH, PE or TPU
Bending Radius	20D
Cable crush resistance	200N/cm long term
Tensile strength	1200N long term
UV resistance	ISO 4892-3
Number of PLC	1to 2pcs
Number of fusion protection sleeve	1to 24pcs
Protection Grade	IP68
Working Temperature	-40°C ~ +80°C

ORDERING INFORMATION

Description	Reference