

Fiber Optic Splice Closure IN-LINE 1IN-1OUT

DESCRIPTION

This kind of box is suitable for the connection of overhead, pipe and buried straight and branch. The box body and base are sealed with hoops and rubber. The closure casing is made of quality engineering plastics, and of good performance of anti-erosion against acid and alkali salt, anti-aging, as well as smooth appearance and reliable mechanical structure. The mechanical structure is reliable and has the performance of resisting wild environment and intensive climate changes and serious working environment. The splice trays (FOST) inside the closure are turnable like booklets, and have adequate curvature radius and space for winding optical fiber to make sure the curvature radius for optical winding 40 mm. Each optical cable and fiber can be operated individually. The product can be opened again and reused after installation.

FEATURES

- Sealing mode: Waterproof sealing rubber strip
- ABS plastic with high strength for better reliability and sealing performance
- Enough space for winding and storing fibers
- IP68 rated for water and dust ingress protection
- Save installation time and improve work efficiency

APPLICATIONS

- Bunchy fibers
- Aerial, underground, wall-mounting, hand hole- mounting, pole-mounting and duct-mounting



SPECIFICATIONS

Item	Fiber Optic Splice Closure IN-LINE 1IN-1OUT
Dimension(mm)	300mm × 125mm × 70mm
Material	ABS
Weight(Kg)	0.56kg
Diameter of Cable(mm)	IN8-12 / OUT 6-12
No. of Cable Inlet/Outlet	1IN-1OUT
Number of Fibers per Tray	12(single core)
Max. Number of Trays	2
Max. Number of Fibers	24(single core)
Sealing of Inlet/Outlet ports	rubber seal
Protection Grade	IP68
Sealing of Shells	Silicon rubber
Working Temperature	-40° C ~ 80° C

ORDERING INFORMATION

Description	Reference