

# Dome Fiber Optic Splice Closure 48F/96F Replaceable Base

## DESCRIPTION

ABL-DCH001 Dome Closure is mainly used for optical fiber connection and protection, it is suitable for connecting overhead, pipe and buried straight and branch. The box body and base are sealed with hoops and rubber. The closure casing is made of highquality engineering plastics, and has good explosion-proof performance against acid and alkali salt, anti-aging, as well as a smooth appearance and reliable mechanical structure. The mechanical structure is reliable and has the ability to withstand the wild environment and intensive climate changes and severe working environment. The splice trays (FOST) inside the closure are turnable like booklets, and have adequate curvature radius and space for winding optical fiber to ensure the curvature radius for optical winding 40 mm. Each cable and fiber can be operated individually. The product can be opened again and reused after installation. Replaceable base support 1 inlet 4 outlet/1 inlet 6 outlet/3 inlet 3 outlet/4 inlet 4 outlet.

## **FEATURES**

- Heat shrinkable sealing and advanced internal structure
- Engineering PP+GF plastic with high strength for better reliability and sealing performance
- Enough space for winding and storing fibers
- Good sealing performance after re-entry and re-use
- Save installation time and improve work efficiency
- Replaceable base

#### **APPLICATIONS**

- $\rightarrow$  Bunchy fibers
- $\rightarrow$  Aerial, buried, underground, vault and building entrance

# SPECIFICATIONS

 •	

FER

Item	Parameters	
Dimension(mm)	500(H)*200mm(D)	
Material	PP+GF	
Weight(Kg)	2kg	
Diameter of Cable(mm)	IN:8-37 OUT: 6-19	
No. of Cable Inlet/Outlet	1 inlet 4 outlet/1 inlet 6 outlet/3 inlet 3 outlet/4 inlet 4 outlet	
Number of Fibers per Tray	24 (single core)	
Max. Number of Trays	4	
Max. Number of Fibers	96 (single core)	
Sealing of Inlet/Outlet ports	Heat shrinkable sealing	
Sealing of Shells	Silicon rubber	
Working Temperature	-40°C~80°C	
Protection Grade	IP68	

#### **ORDERING INFORMATION**

Description	Reference
48F Fiber splice closure, Dome type, Heat shrinkable seal ,Replaceable base, 1 inlet 4 outlet/1 inlet 6 outlet/3 inlet 3 outlet/4 inlet 4 outlet	ABL-DCH001-48C
96F Fiber splice closure, Dome type, Heat shrinkable seal ,Replaceable base, 1 inlet 4 outlet/1 inlet 6 outlet/3 inlet 3 outlet/4 inlet 4 outlet	ABL-DCH001-96C