

NSN Boot LC Duplex 2F LSZH Outdoor Cable

DESCRIPTION

NSN Boot Optic Patch Cord cable is available with 90 degrees and straight duplex to connect the Nokia Simens RRH panels. It is the ideal design for outdoor fiber cable applications. Such product can meet the FTTA (fiber to the Antenna) program requirements for outdoor environment conditions. Compatible with Nokia's waterproof connector for latest and next-generation mobile communication systems. Especially in the 3G, 4G,5G Base station (BBU to RRU).

FEATURES

- Factory-assembled cables for a fast on-site installation
- Flexibility with small bending radius and excellent cable routing properties
- The material in the jumpel cable are all-weather and UV-resistant

APPLICATIONS

- Multi-purpose Outdoor
- For connection between distribution box and RRH
- Deployment in Remote Radio Head cell tower applications
- Outdoor FTTP, FTTA connection
- Industrial outdoor applications



SPECIFICATIONS

Item	Miian Parameters	
	SM	MM
Insertion Loss	Typical≤0.15dB;Max≤0.30dB	Typical≤0.15dB;Max≤0.30dB
Return Loss	≥50dB(UPC), ≥60dB(APC)	≥30dB(UPC)
Cable Count	2	
Out sheath Diameter	5.0±0.2mm	
Min. Tensile Strength	800N (short term), 400N (long term)	
Min. Crush Load	2000N (short term), 1000N (long term)	
Min. Bending Radius	20D (short term), 10D (long term)	
Storage Temperature	-20°C~+70°C	
Humidity	+40°C at 93%, 96h duration	

ORDERING INFORMATION

Description	Reference